


MODEL
EMC / EMWThe **SOLUTIONS**
for **LIGHT DUTY**
APPLICATIONS**EMC & EMW Models****300 & 500 lb.****Made in USA****500 lb.****Made in USA**

COFFING EMC & EMW Models - Compact chain and wire rope hoists designed for a variety of light duty applications. These models feature thermally protected motors.

CAPACITIES & LIFT - Rated loads 300 and 500 pounds. 10-foot lift with 6-foot push button cord standard.

VOLTAGES - 115V, single phase motors only.

SUSPENSION - Swivel top and bottom hooks with safety latches standard.

POWER CORD - Provided with grounded 3-prong plug for easy installation in any standard 115V outlet.

ALUMINUM HOUSING - Lightweight and compact to provide strength and portability. Weighs less than 25 lb.

LIMIT SWITCHES - Upper and lower limit switches on chain models and upper paddle limit switch on wire rope model regulates load travel.

ELECTROMAGNETIC BRAKE - Quick acting for positive load control.

THERMAL MOTOR PROTECTION - Standard to prevent overheating.

LIGHT DUTY OPERATION - Rated for intermittent duty applications (10-minute run time per hour maximum).

ACCESSORIES - LCC-05 chain container (shown) available for EMC models.

UL LISTED

LIFETIME WARRANTY

• SPECIFICATIONS •

EMC & EMW Models

Capacity (lb.)	Model Number	No. of Chains	Standard Lift (ft.)	Motor HP	Lift Speed (fpm)	Headroom (in.)	Housing Dimensions (in.)			Net Wt. (lb.)
							H	W	L	
300	EMC-300B	1	10	1/6	16	14 1/2	4 3/8	6 3/8	14 1/4	21
500	EMC-500B	2	10	1/6	8	16	4 3/8	6 3/8	14 1/4	24
500	EMW-500B	2-part wire rope	10	1/6	16	13 3/4	4 3/8	6 3/8	14 1/4	19

Note: For complete dimensional data, refer to Coffing Dimensional Databook